

Adflex V 109 F

Advanced Polyolefin

Product Description

Adflex V 109 F is a reactor TPO (thermoplastic polyolefin) manufactured using LyondellBasell's proprietary *Catalloy* process technology. It is primarily used for molding, impact modification, extrusion coating and film applications. This resin can be used on conventional injection molding or extrusion equipment.

Adflex V 109 F features a very high softness and low modulus, with a relatively high melt flow. The grade is available in natural pellet form.

For regulatory compliance information, see the *Adflex V 109 F Product Stewardship Bulletin* (PSB).

Product Characteristics

Status	Commercial: Active
Test Method used	ISO
Availability	North America
Processing Methods	Cast Film, Injection Molding
Features	Clarity, Contact, Low Temperature Impact Resistance, Soft
Typical Customer Applications	Film Wrap, Housewares, Industrial, Roofing Underlayment, Sports, Leisure and Toys

Typical Properties	Method	Value	Unit
Physical			
Density (Method A)	ISO 1183	0.89	g/cm ³
Melt flow rate (MFR) (230 °C/ 2.16 kg)	ISO 1133	12	g/10 min
Mechanical			
Tensile Stress at Break	ISO 527-1, -2	8	MPa
Tensile Stress at Yield	ISO 527-1, -2	5	MPa
Tensile Strain at Break	ISO 527-1, -2	> 800	%
Tensile Strain at Yield	ISO 527-1, -2	> 40	%
Flexural modulus	ISO 178	80	MPa
Impact			
Notched izod impact strength (- 40°C, Type 1, Notch A)	ISO 180	2	kJ/m ²
(23 °C, Type 1, Notch A)		No Break	
Ductile/Brittle transition temperature	ISO 6603-2	-55	°C
Hardness			
Shore hardness (Shore A)	ISO 868	85	
Shore hardness D	ISO 868/ASTM D 2240	30	
<i>Note: 15 seconds</i>			
Thermal			
Heat deflection temperature B (0.45 MPa) Unannealed	ISO 75B-1, -2	35	°C
Vicat softening temperature (A50 (50°C/h 10N) °C)	ISO 306	55	°C
Melting temperature	DSC	142	°C
<i>Note: ISO 11357-3</i>			

Additional Properties

Tear Strength (Graves, Die C, 50 mm/min), ASTM D 624: 65 N/mm
Load/Width @ Max Load
Mold Shrink, ISO 294-4: 0.9 %
48 hr after molding, 100 mmx150 mmx3.2 mm plaque

Notes

Typical properties; not to be construed as specifications.

- Basell Sales & Marketing Company B.V.
- Basell Asia Pacific Limited
- Basell International Trading FZE
- LyondellBasell Australia Pty Ltd

For the contact details of the LyondellBasell company selling this product in your country, please visit <http://www.lyb.com/>.

Before using a product sold by a company of the LyondellBasell family of companies, users should make their own independent determination that the product is suitable for the intended use and can be used safely and legally.

SELLER MAKES NO WARRANTY; EXPRESS OR IMPLIED (INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY WARRANTY) OTHER THAN AS SEPARATELY AGREED TO BY THE PARTIES IN A CONTRACT.

This product(s) may not be used in:

(i) any U.S. FDA Class I, Health Canada Class I, and/or European Union Class I Medical Devices, without prior notification to Seller for each specific product and application; or

(ii) the manufacture of any of the following, without prior written approval by Seller for each specific product and application: (1) U.S. FDA Class II, Health Canada Class II or Class III, and/or European Union Class II Medical Devices; (2) film, overwrap and/or product packaging that is considered a part or component of one of the aforementioned Medical Devices; (3) packaging in direct contact with a pharmaceutical active ingredient and/or dosage form that is intended for inhalation, injection, intravenous, nasal, ophthalmic (eye), digestive, or topical (skin) administration; (4) tobacco related products and applications; (5) electronic cigarettes and similar devices; and (6) pressure pipe or fittings that are considered a part or component of a nuclear reactor.

(iii) Additionally, the product(s) may not be used in: (1) U.S. FDA Class III, Health Canada Class IV, and/or European Class III Medical Devices; (2) applications involving permanent implantation into the body; (3) life-sustaining medical applications; and (4) lead, asbestos or MTBE related applications.

All references to U.S. FDA, Health Canada, and European Union regulations include another country's equivalent regulatory classification.

Users should review the applicable Material Safety Data Sheet before handling the product.

Addhere, Adflex, Adstif, Adsyl, Akoafloor, Akoalit, Alastian, Alathon, Alkylate, Amazing Chemistry, Aquamarine, Aquathene, Arctic Plus, Arctic Shield, Avant, Catalloy, Clyrell, CRP, Crystex, Dexflex, Duopac, Duoprime, Explore & Experiment, Filmex, Flexathene, Fueling the power to win, Get in touch with, Glacido, Hifax, Histif, Hostacom, Hostalen PP, Hostalen ACP, Ideal, Indure, Integrate, Koattro, LIPP, Lucalen, Lufflexen, Lupolen, Lupolex, Luposim, Lupostress, Lupotech, Metocene, Microthene, Moplen, MPDIOL, Nerolex, Nexprene, Petrothene, Plexar, Polymeg, Pristene, Prodflex, Pro-fax, Punctilious, Purell, Refax, SAA100, SAA101, Sequel, Softell, Spherilene, Spheripol, Spherizone, Starflex, Stretchene, Superflex, TBAC, Tebol, T-Hydro, Topyl, Trans4m, Tufflo, Ultrathene, Vacido and Valtec, are trademarks owned and/or used by the LyondellBasell family of companies.

Adsyl, Akoafloor, Akoalit, Alastian, Alathon, Aquamarine, Arctic Plus, Arctic Shield, Avant, CRP, Crystex, Dexflex, Duopac, Duoprime, Explore & Experiment, Filmex, Flexathene, Hifax, Hostacom, Hostalen, Ideal, Integrate, Koattro, Lucalen, Lupolen, Metocene, Microthene, Moplen, MPDIOL, Nexprene, Petrothene, Plexar, Polymeg, Pristene, Pro-fax, Punctilious, Purell, Sequel, Softell, Spheripol, Spherizone, Starflex, Tebol, T-Hydro, Topyl, Tufflo, Ultrathene are registered in the U.S. Patent and Trademark Office.

Release Date: 24 May 2013