



PRIMACOR™ 3460 Copolymer

Overview PRIMACOR™ 3460 Copolymer is an ethylene acrylic acid copolymer suitable for extrusion coating and extrusion lamination applications.

PRIMACOR 3460 Copolymer has been specifically designed for use as a sealant and adhesive layer in flexible packaging laminates and thin paper coating.

PRIMACOR 3460 Copolymer exhibits:

- Excellent heat sealability and hot tack.
- Excellent adhesion to metallic, paper and PE substrates.
- Good stress crack resistance.
- Designed specifically for high line speeds and low processing temperature.
- Insensitive to moisture.

Note:

PRIMACOR 3460 Copolymer should comply with FDA regulation 177.1310 and with most European food contact regulations when used unmodified and processed according to good manufacturing practices for food contact applications. Please contact your nearest office regarding food contact compliance statements. The purchaser remains responsible for determining whether the use complies with all relevant regulations.

Applications:

- Flexible packaging.
- Thin paper coating.
- Metallic substrate lamination.

Physical	Nominal Value (English)	Nominal Value (SI)	Test Method
Density	0.938 g/cm ³	0.938 g/cm ³	ASTM D792 ISO 1183
Melt Index (190°C/2.16 kg)	20 g/10 min	20 g/10 min	ISO 1133 ASTM D1238 ¹
Comonomer Content	9.7 %	9.7 %	Dow Method ²
Mechanical	Nominal Value (English)	Nominal Value (SI)	Test Method
Tensile Strength			ASTM D638 ISO 527-2
Yield, Compression Molded	1050 psi	7.24 MPa	
Break, Compression Molded	2350 psi	16.2 MPa	
Tensile Elongation			ASTM D638 ISO 527-2
Break, Compression Molded	580 %	580 %	
Films	Nominal Value (English)	Nominal Value (SI)	Test Method
Seal Initiation Temperature	185 °F	85.0 °C	Dow Method ³
Water Vapor Transmission Rate 100°F (38°C), 90% RH	1.1 g-mil/100in ² /at m/24 hr	0.44 g-mm/m ² /atm/ 24 hr	DIN 53122/2
Thermal	Nominal Value (English)	Nominal Value (SI)	Test Method
Vicat Softening Temperature	162 °F	72.2 °C	ASTM D1525 ISO 306
Melting Temperature (DSC)	203 °F	95.0 °C	Dow Method

Additional Information

Specific test settings in accordance to Inter Laboratory Round Robin programs with method priorities for ISO/ASTM.

Extrusion	Nominal Value (English)	Nominal Value (SI)	Test Method
Melt Temperature	428 to 500 °F	220 to 260 °C	
Minimum Coating Thickness	0.400 mil	0.400 mil	Dow Method
Minimum Coating Weight	6.0 lb/ream	9.8 g/m ²	Dow Method
Neck-in			Dow Method
550°F (288°C), 0.00100 in (0.0254 mm)	2.8 in	7.1 cm	

Extrusion Notes

Fabrication Conditions For Extrusion Coating Film:

Equipment used to process this resin should be constructed of corrosion resistant materials. Dies and adapters are recommended to be stainless steels and/or duplex chrome or nickel plated.

- Screw Size: 3.5 in. (89 mm); 30:1 L/D
- Die: 30 inch die deckled to 24 inches
- Die Gap: 20 mil (0.508 mm)
- Melt Temperature: 425°F (218°C)
- Output: 250 lb/hr
- Air Gap: 6 in. (152 mm)

Notes

These are typical properties only and are not to be construed as specifications. Users should confirm results by their own tests.

¹ As measured at the time of production.

² Comonomer content measured by a DOW proprietary method that has equivalent accuracy as compared to ASTM D 4094.

³ 25 g/m² coatings at 290°C set temperature.

Product Stewardship

The Dow Chemical Company and its subsidiaries ("Dow") has a fundamental concern for all who make, distribute, and use its products, and for the environment in which we live. This concern is the basis for our Product Stewardship philosophy by which we assess the safety, health, and environmental information on our products and then take appropriate steps to protect employee and public health and our environment. The success of our Product Stewardship program rests with each and every individual involved with Dow products — from the initial concept and research, to manufacture, use, sale, disposal, and recycle of each product.

Customer Notice

Dow strongly encourages its customers to review both their manufacturing processes and their applications of Dow products from the standpoint of human health and environmental quality to ensure that Dow products are not used in ways for which they are not intended or tested. Dow personnel are available to answer your questions and to provide reasonable technical support. Dow product literature, including safety data sheets, should be consulted prior to use of Dow products. Current safety data sheets are available from Dow.

Medical Applications Policy

NOTICE REGARDING MEDICAL APPLICATION RESTRICTIONS: Dow will not knowingly sell or sample any product or service ("Product") into any commercial or developmental application that is intended for:

- long-term or permanent contact with internal bodily fluids or tissues. "Long-term" is contact which exceeds 72 continuous hours;
- use in cardiac prosthetic devices regardless of the length of time involved ("cardiac prosthetic devices" include, but are not limited to, pacemaker leads and devices, artificial hearts, heart valves, intra-aortic balloons and control systems, and ventricular bypass-assisted devices);
- use as a critical component in medical devices that support or sustain human life; or
- use specifically by pregnant women or in applications designed specifically to promote or interfere with human reproduction.

Dow requests that customers considering use of Dow products in medical applications notify Dow so that appropriate assessments may be conducted. Dow does not endorse or claim suitability of its products for specific medical applications. It is the responsibility of the medical device or pharmaceutical manufacturer to determine that the Dow product is safe, lawful, and technically suitable for the intended use. **DOW MAKES NO WARRANTIES, EXPRESS OR IMPLIED, CONCERNING THE SUITABILITY OF ANY DOW PRODUCT FOR USE IN MEDICAL APPLICATIONS.**

Disclaimer

NOTICE: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, the Customer is responsible for determining whether products and the information in this document are appropriate for the Customer's use and for ensuring that the Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Dow assumes no obligation or liability for the information in this document. **NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.**

NOTICE: If products are described as "experimental" or "developmental": (1) product specifications may not be fully determined; (2) analysis of hazards and caution in handling and use are required; (3) there is greater potential for Dow to change specifications and/or discontinue production; and (4) although Dow may from time to time provide samples of such products, Dow is not obligated to supply or otherwise commercialize such products for any use or application whatsoever.

Additional Information

North America		Europe/Middle East	+800-3694-6367
U.S. & Canada:	1-800-441-4369		+32-3-450-2240
	1-989-832-1426	Italy:	+800-783-825
Mexico:	+1-800-441-4369		
Latin America		South Africa	+800-99-5078
Argentina:	+54-11-4319-0100		
Brazil:	+55-11-5188-9000		
Colombia:	+57-1-219-6000	Asia Pacific	+800-7776-7776
Mexico:	+52-55-5201-4700		+603-7965-5392

www.dowplastics.com

This document is intended for use within Asia Pacific, Europe, North America

Published: 1995-11-01

© 2009 The Dow Chemical Company

